



TECHNICAL SPECIFICATION

RANGE: ARTICULATE

TILE CONSTRUCTION

PRODUCTION METHOD

Pattern loop

YARN CONTENT

EarthSmart Refresh Fibre
Solution Dyed Nylon with 30%
recycled content

PRIMARY BACKING

Non woven

TILE BACKING

Vinyl (contains recycled content)

GAUGE

1/12

TOTAL THICKNESS

6.35mm

PILE HEIGHT

4mm

TOTAL WEIGHT

4285 gr/m² (126.37oz sq yd)

PILE WEIGHT

610g/m² (18oz/sq. yd.)

TILE SIZE

610 x 610mm (24" x 24")

CLASSIFICATION

PROJECT RATING

Heavy contract

TEST RESULTS

STATIC CONTROL

Life of the carpet protection.
Less than 3.5kv Antistatic warranted
for the life of the carpet

SURFACE SPREAD OF FLAME

ASTM E-648
ASTM E-662

Flooring radiant panel – class 1
NBS smoke chamber test

GREEN

GLP1922

Articulate is certified PLATINUM by
the NSF 140-2007 Sustainable
Carpet Standard
Carpet & Rug Institute's indoor Air
Quality Green Label Carpet

WARRANTY

10 year limited wear warranty

