



## TECHNICAL SPECIFICATION

### RANGE: COASTLAND

#### TILE CONSTRUCTION

PRODUCTION METHOD		Tufted patterned loop
YARN CONTENT		100% solution dyed nylon
PRIMARY BACKING		PET woven
SECONDARY BACKING		Bitumen
TOTAL THICKNESS	ISO 1765	± 9.0mm
PILE HEIGHT	ISO 1766	± 2.6mm
TOTAL WEIGHT		4920 gr/m <sup>2</sup>
TUFTED YARN WEIGHT		810 gr/m <sup>2</sup>
TILE SIZE		500 x 500mm

#### CLASSIFICATION

PROJECT RATING	BS EN 1307	Heavy commercial class 33
----------------	------------	---------------------------

#### TEST RESULTS

STATIC CONTROL		Permanently anti-static
IMPACT NOISE REDUCTION	ISO 140-8	24 dB
HORIZONTAL RESISTANCE	ISO CD 10965	3x10 <sup>8</sup> Ohm
VERTICAL RESISTANCE	ISO CD 10965	4x10 <sup>10</sup> Ohm
SURFACE SPREAD OF FLAME	EN ISO 9239-1	Bfl-s1
THERMAL ISOLATION	ISO 8302	0.088 m <sup>2</sup> kW

#### FASTNESS

LIGHT FASTNESS	ISO 105 B02	>5
WATER FASTNESS	ISO 105 E01	4-5
RUBBING FASTNESS	ISO 105 X12	4-5

#### WARRANTY

10 year limited wear warranty

