



## TECHNICAL SPECIFICATION

### RANGE: ELEMENTAL

#### BROADLOOM CONSTRUCTION

PRODUCTION METHOD	Tip sheared patterned loop
YARN CONTENT	100% Universal Fibres Type 6.6 nylon with Permanent Stain Resist
PRIMARY BACKING	Polypropylene
SECONDARY BACKING	Action Bac
GAUGE	1/12
TOTAL THICKNESS	(approx.) 7.5mm
PILE HEIGHT	(approx.) 6.5mm
APPROXIMATE TOTAL WEIGHT	2245 gr/m <sup>2</sup> (66.2oz / sq yd)
PRESHEARED TUFTED YARN WEIGHT	1085 gr/m <sup>2</sup> (32oz / sq yd)
WIDTH	3.66m – 12'
PATTERN REPEAT	45.72cm (W) x 27.94cm (L)

#### CLASSIFICATION

PROJECT RATING	Heavy contract
----------------	----------------

#### TEST RESULTS

STATIC CONTROL	Less than 3.5 k. Antistatic warranted for the life of the carpet
SURFACE SPREAD OF FLAME	Flooring radiant panel – class 1 ASTM E-648 NBS smoke chamber – Pass ASTM E-622

#### ENVIRONMENTAL

Emit meets the standards for the Carpet  
& Rug Institute's Indoor Air Quality  
Green Label Plus Caret Testing  
Program

Emit is 3<sup>rd</sup> party certified by the NSF-  
140 Sustainable Carpet Standard

#### WARRANTY

10 year limited wear warranty

