

TECHNICAL SPECIFICATION

RANGE: BESPOKE, CADENCE & TREAD



CONSTRUCTION

PRODUCTION METHOD	Patterned loop pile
YARN CONTENT	100% Universal Fibres Type 6,6 nylon (with option to be made with Thrive® by Universal Fibers®)
PRIMARY BACKING	Synthetic
SECONDARY BACKING	EarthWise
PILE HEIGHT	approx. 7.4mm
TOTAL WEIGHT	3468 gr/m ² (102oz/sqyd)
TUFTED YARN WEIGHT	542 gr/m ² (16oz/sqyd)
CARPET TILE SIZE	60.96cm x 60.96cm (24" x 24")
RECOMMENDED INSTALLATION	Monolithic

CLASSIFICATION

PROJECT RATING	Heavy contract
----------------	----------------

TEST RESULTS

STATIC CONTROL	Less than 3.5 kV. Antistat warranted for the life of the carpet.
----------------	---

FLAMABILITY RATINGS

Flooring radiant panel – ASTM E-648
Passes NBS smoke chamber – ASTM
E-662

ANTISOIL TREATMENT

Permanent Stain Resist

QUALITY ASSURANCE

Bespoke, Cadence & Tread meet the
standards for the Carpet & Rug
Institute's Indoor Air Quality Green
Label Plus Carpet Testing Program.

Bespoke, Cadence & Tread are 3rd
party certified to the NSF-140
Sustainable Carpet Standard.

WARRANTY

10 year limited wear warranty

