



**TECHNICAL SPECIFICATION  
RANGE: STRAIGHT & NARROW**

**TILE CONSTRUCTION**

PRODUCTION METHOD	DIN 61151	Tufted textured linear loop
YARN CONTENT		100% Lumena solution dyed (type 6.6)
PRIMARY BACKING		PA/PES – non woven colbac
SECONDARY BACKING	DIN 61151	Bitumen
TOTAL THICKNESS	DIN 53855	± 7.0mm
PILE HEIGHT	DIN 54325	± 4.0mm
TOTAL WEIGHT		4400 gr/m <sup>2</sup>
TUFTED YARN WEIGHT		700 gr/m <sup>2</sup>
TILE SIZE		500 x 500mm

**CLASSIFICATION**

PROJECT RATING	BSEN 1307	Class 33 Heavy commercial use
	BSEN 1307	Luxury Class LC2
CASTOR CHAIR	DIN 54324	Pass
LISSON TEST	DIN	Pass

**TEST RESULTS**

STATIC CONTROL		Permanently anti-static
	BS ISO 10965	Static dissipative
IMPACT NOISE REDUCTION	DIN 52210	25 dB
IBM/ICL		Pass
HORIZONTAL RESISTANCE	NEN 6167	4.10
VERTICAL RESISTANCE	NEN 6167	3.10
SURFACE SPREAD OF FLAME	DIN 4102	B1
FIRE BEHAVIOUR	EN 13501	Cfl-s1 C E

**WARRANTY**

10 year limited wear warranty

**ENVIRONMENTAL**

ENP 447	BRE Environmental profiles certification
150218-01	CRI Green Label Plus compliant

