



**TECHNICAL SPECIFICATION
RANGE: STRESSED OUT**

TILE CONSTRUCTION

PRODUCTION METHOD	DIN 61151	Tufted textured linear loop
YARN CONTENT		100% Lumena solution dyed (type 6.6)
PRIMARY BACKING		PA/PES – non woven colbac
SECONDARY BACKING	DIN 61151	Bitumen
TOTAL THICKNESS	DIN 53855	± 7.0mm
TOTAL WEIGHT		4715 gr/m ²
TUFTED YARN WEIGHT		700 gr/m ²
TILE SIZE		500 x 500mm

CLASSIFICATION

PROJECT RATING	BSEN 1307	Heavy Commercial class 33
	BSEN 1307	Luxury Class LC2
CASTOR CHAIR	DIN 54324	Pass
LISSON TEST	DIN	Pass

TEST RESULTS

STATIC CONTROL		Permanently anti-static
	BS ISO 10965	Static dissipative
IMPACT NOISE REDUCTION	DIN 52210	25 dB
IBM/ICL		Pass
HORIZONTAL RESISTANCE	NEN 6167	4.10
VERTICAL RESISTANCE	NEN 6167	3.10
SURFACE SPREAD OF FLAME	DIN 4102	B1
FIRE BEHAVIOUR	EN 13501	Cfl-s1 C E
LIGHT FASTNESS	DIN 54004	5-7
WATER FASTNESS	DIN 54006	4-5

WARRANTY

10 year limited wear warranty

ENVIRONMENTAL

ENP 525

BRE Environmental profiles certification

