

## TECHNICAL SPECIFICATION

**RANGE: TOP- NOTCH, TOP- SHELF, TIP- TOP (broadloom)**



### BROADLOOM CONSTRUCTION

PRODUCTION METHOD	Patterned loop
YARN CONTENT	Thrive® by Universal Fibers®. Nylon 6,6 with 75% recycled content and permanent stain resistance.
PRIMARY BACKING	Woven Polypropylene
SECONDARY BACKING	Woven Polypropylene with Unitary
GAUGE	1/12
TOTAL THICKNESS	N/A
PILE HEIGHT	(approx.) 7.4mm
APPROXIMATE TOTAL WEIGHT	2380 g/m <sup>2</sup> (70.2 oz./Sq. Yd.)
WIDTH	3.66m – 12'
PATTERN REPEAT	TN: 121.92cm x 106.68cm TS: 121.92cm x 101.6cm TT: 60.96cm x 35.56cm

### CLASSIFICATION

PROJECT RATING Heavy contract

### TEST RESULTS

STATIC CONTROL Less than 3.5kV. Antistatic warranted for the life of the carpet.

SURFACE SPREAD OF FLAME

Flooring radiant panel – class 1  
ASTM E-648

NBS smoke chamber – Pass  
ASTM E-662

GREEN

Top- Notch, Top- Shelf & Tip- Top  
are certified by the NSF 140  
Sustainable Carpet Standard.

Top- Notch, Top- Shelf & Tip- Top  
meet the standards for the Carpet &  
Rug Institute's indoor Air Quality  
Green Label Plus Carpet Testing  
Program



